








and THE GAVDOS TEAM








Abstract The Gavdos permanent absolute calibration facility, initially established with joint EU, NASA, and Swiss Federal Government funding in 2002, while fully

operational at the moment, it is also being expanded to a regional absolute sea level monitoring and altimeter calibration facility applicable to many missions, in the Eastern Mediterranean. The main site is still at Karave, located under a crossing point adjacent to an ENVISAT pass, on the isle o vdos, about 50 km to the south of the main isla of Crete, Greece. The project is now continuing under the OSTM program with funding from NASA and the Greek government. The current plans include the relocation of the Gavdos "Karave" facility to the final and originally intended location, on a new pier (finally constructed!), a move that will improve vastly the protection of the facility from heavy winter storms and minimize the need for maintenance. The Karave GPS receiver operated continuously throughout the past years, the tide gauges however were placed in storage to avoid damage during the construction period, and they have been redeployed as of last fall. The facility now has "off the wall" electric power at all times, and it will be upgraded to include an ISDN line and a computer, so that we will be able to download all of the data, including GPS observations, on a hourly/daily basis. This is expected to happen in early 2007. We have already selected the location for the establishment of an identical setup at a site on the main island of Crete, at Kastelli, near the TUC site (60 km west of TUC), on a TUC-owned area and situated exactly under the descending Jason-1 pass 018. We have selected a radar gauge as well as a backup system of similar type for the new location. Once tested and calibrated, we plan to replace the Karave system with one of these since they are much less demanding in terms of maintenance, always a concern during the winter months. This gives us access to a second site and use of the altimeter measurements made to the

Cretan esults on the efforts to also tion at the TUC ch Transportable Laser Rand em (FTLRS) that established an initial link of t GAVDOS network of sites with the ITRF200 in order to update the link to the global TR is contingent on FTLRS' availability, which in tied to its deployment in Australia and the unch of JASON-2.

Aegean Sea. It will thus allow



Mertikas, S. P., E. C. Pavlis and P. Drakopoulos. 2003. GAVDOS: A satellite radar altimeter calibration and sea-level monitoring site on the island of Gavdos, Crete, H. Dahlin, N.C. Flemming, K. Nittis, S.E. Petersson eds. Building the European Capacity in Operational Oceanography, Proceedings of the 3rd EuroGOOS Conference, 3-6 December 2002, Athens, Greece, pp. 258-264, Elsevier Oceanography Series 69.

rmation on the JASON Re-Calibrations over Gavdos for Cycles 70-90 between the

And the second sec	and the second	and the second	
Geocentric Coords. & Epoch	X	У	Z 🤶
GVD0 @ 2004.6	4783636.3296 ±0.0003	2140711.9860 ±0.0002	3623246.2746 ±0.0002
Rates [mm/yr]	North: -25.98 ±0.08	East: -14.40 ±0.16	Up: -2.00 ±0.37
GVD5 @ 2004.6	4782619.7314±0.0003	2141235.1602±0.0002	3624092.1771±0.0003
Rates [mm/yr]	North: -26.50 ±0.15	East: -15.67 ±0.28	Up: -1.40 ±0.66

ITRF2005 Re-Analysis New GDRs from GDR-A + Corrections (≈ GDR-B)

Coordinates converted to ITRF2005 (Helmert-transformed)

ITRF2005 Orbits (GSFC, Luthcke et al.)

JMR corrections (Desai model**)**

New Parametric SSB (ITRF2005-compatible, Beckley/GSFC)

Revised Gavdos GVD5 Height:

21.7750 m

Summary

The 2006 re-analysis of the Gavdos GPS network data with an extended set of 3 years of data and the strict "navigation" of the sites in the ITRF2000 TRF, resulted in a 13 mm reduction of the estimated JASON-1 bias. A small correction of 2 mm was also applied, based on the SLR monitoring of the origin of the TRF wrt the "geocenter".

Following the release of the new TRF, ITRF2005, in late 2007, we have initiated a new reanalysis of the GPS data to produce coordinates for all of our network sites, compatible with the new ITRF. In the meantime, as a first step, we have generated the ITRF2005 coordinates for all these sites, using the standard ITRF2000-to-ITRF2005 Helmert similarity transformation parameters available from ITRS.

The adoption of the new coordinates allows us to use the newly available GDRs from NASA Goddard [B. Beckley], based on improved ITRF2005 orbits, corrected for JMR errors and using an ITRF2005consistent parametric SSB model [B. Beckley].

Pavlis, E. C. 1999. Tectonics, Sea-level Monitoring and Altimeter Calibration With a Regional GPS Array, G. Maul ed. Proc. of the International Symposium on Marine Positioning, INSMAP 98, Nov. 30 – Dec. 4, 1998, Melbourne, Florida.

Pavlis, E. C., S. P. Mertikas and the GAVDOS Team. 2004. The GAVDOS Mean Sea Level and Altimeter Calibration Facility: Results for Jason-1, 3rd Jason special issue, Mar. Geod., (27), 3-4, DOI:10.1080/01490410490902106, pp. 631-655.

Somieski, A., B. Buerki, A. Geiger, H.-G. Kahle, E. C. Pavlis, H. Becker-Ross, S. Florek and M. Okruss. 2006. Tropospheric Water Vapor from Solar Spectrometry, and Comparison with JASON Microwave Radiometer Measurements, accepted, J. of Geophys. Res., (Atmospheres).



Previous Gavdos GVD5 Height: 21.7620 m **Ah Correction to previous Bias :** -0.0130 m **Ah Correction due to TRF change: 0.0246 m** Δh due to ΔGDR from v.A to \approx v.B (GSFC) (cycle dependent)

REVISED CALIBRATED BIAS: 121 ± 10 mm

2007 Ocean Surface Topography Science Team Meeting

Wrest Point • Hobart, Australia • March 12 - 15, 2007

The net effect of all these changes resulted in a revised bias value of 121 ± 10 mm on the basis of our data set for cycles 70 through 90.

The new jetty at Karave was recently completed, and the instruments were successfully re-deployed in November of 2006. The new data will evaluated as soon as the corresponding GDRs are available.

We are proceeding with the instrumentation of our second location on mainland Crete, at Kasteli, where a second calibration facility will be constructed this spring and functional by this summer.

