



## Systematic Calval SWIM - CFOSAT

CNES, CASYS

Synthesis report on parameters quality: cycle 60 (2020-12-07 - 2020-12-20)



# Contents

<b>I</b>	<b>Introduction</b>	<b>3</b>
1	Context	4
2	Glossary	5
<b>II</b>	<b>Instrumental</b>	<b>6</b>
3	Review	7
4	Instrument mode and House Keeping	8
5	CAL1 internal sequence	10
6	Antenna rotation speed	12
<b>III</b>	<b>Coverage</b>	<b>13</b>
7	Coverage nadir 5Hz	14
8	Coverage off-nadir	15
<b>IV</b>	<b>Editing</b>	<b>16</b>
9	Nadir 5Hz Nsec	17
10	Off-nadir	19
<b>V</b>	<b>SWIM nadir monitoring</b>	<b>21</b>
11	Current cycle maps of valid SWH and wind speed	22
11.1	Current cycle map of valid SWH . . . . .	22
11.2	Current cycle map of wind speed . . . . .	23
12	SWIM nadir versus ECMWF model	24
12.1	Long term monitoring along track for SWH . . . . .	24
12.2	Current cycle map of SWH difference with ECMWF model . . . . .	24
13	Wind speed versus ECMWF model	26
13.1	Long term monitoring along track for wind speed . . . . .	26
13.2	Current cycle map of Wind speed difference with ECMWF model . . . . .	26

<b>14 CFOSAT/SWIM nadir versus AL and J3 at crossovers (3h)</b>	<b>27</b>
14.1 Long term monitoring along track SWH (CFO/AL/J3) . . . . .	27
14.2 Long term monitoring along track sigma0 (CFO/AL/J3) . . . . .	28
14.3 Long term monitoring along track wind (CFO/AL/J3) . . . . .	28
 <b>VI SWIM off-nadir monitoring</b>	 <b>29</b>
<b>15 SWIM off-nadir current cycle maps per beam</b>	<b>30</b>
15.1 SWH . . . . .	30
15.2 Wavelength . . . . .	30
15.3 Direction . . . . .	31
 <b>16 SWIM off-nadir versus models</b>	 <b>32</b>
16.1 SWIM SWH versus ECMWF SWH . . . . .	32
16.1.1 Current cycle maps of differences with ECMWF model . . . . .	32
16.1.2 Long term monitoring along track . . . . .	33
16.2 SWIM wavelength versus MFWAM wavelength . . . . .	33
16.2.1 Current cycle maps of differences with MFWAM . . . . .	33
16.2.2 Long term monitoring along track . . . . .	33
16.3 SWIM direction versus MFWAM direction . . . . .	34
16.3.1 Current cycle maps of differences with MFWAM . . . . .	34
16.3.2 Long term monitoring along track . . . . .	35
 <b>17 SWIM off-nadir versus Sentinel-1</b>	 <b>36</b>
17.1 SWH . . . . .	36
17.2 Wavelength . . . . .	37

Main Part I

Introduction



# Part 1

## Context

**Document overview** This document reports the major features that characterize the quality of SWIM/CFOSAT data. It is released on a cyclic basis.

The main goals of the document are:

- to report any changes in software and data processing;
- to present the main instrumental parameters;
- to provide insights on data quality and coverage.

**Software version** This cycle was produced with:

- product version: 6.0.3;
- CDB version: 23\_32;
- CASYS version: 6.0.2.

**Specific events** SWIM was operated in Speckle mode from December 7th, 2020 to December 12th, 2020, together with non-nominal modes (see page 8) from December 8th, 2020 at 00:00 to December 11th, 2020 at 23:59:59, resulting in missing data for the off-nadir beams. In addition, during a special program (antenna rotation stopped to target a reflector in the area of Toulouse) on December 8th, 2020 from 18:19 to 18:41, and on December 9th, 2020 from 07:24 to 07:46, SWIM was operated in a non-nominal mode ("0-8-8" mode). Missing data on December 9th, 2020 from 02:36 to 04:22, due to missing NADIR products.

**Long term monitoring** Statistics are provided on a long-term prospect, starting from April 19th, 2019 (cycle 14).

Table 1.1: Dates of AWWAIS' versions

AWWAIS version	Date
AWWAIS 4.0.2	06/11/2018 00:00:00
AWWAIS 4.1.1	18/12/2018 11:00:00
AWWAIS 4.2.1	12/03/2019 14:00:00
AWWAIS 4.2.2	23/04/2019 16:00:00
AWWAIS 4.3.1	16/07/2019 05:33:00
AWWAIS 5.0.1	24/06/2020 11:57:26
AWWAIS 5.1.1	12/10/2020 13:30:00
AWWAIS 5.1.2	16/11/2020 14:00:00
AWWAIS 5.2.0	27/07/2021 06:53:21

## Part 2

# Glossary

**Track, Pass** refers to a half-orbit of CFOSAT.

**Cycle** refers to the 13-day period that takes CFOSAT to come back to the same position.

**AWWAIS** SWIM processing chain in the French ground segment associated with a version number.

Main Part II

Instrumental

## Part 3

# Review

The following table summarizes the performance of the SWIM instrument during the current cycle and gives notice of possible incidents.

	Parameter	Comments
1	Operating modes	The operating mode is OK (normal tracking sequences and calibration modes) Data missing Dec 9 02:39 - 04:14
2	Macrocycle configuration	0°, 2°, 4°, 6°, 8°, 10° 0°, 2°, 8°, 8°, Dec 8 00:00 - Dec 9 23:59 0°, 8°, 8°, Dec 8 18:19 - 18:40 and Dec 9 07:31 - 07:40 0°, 2°, 10°, 10°, Dec 10 00:00 - Dec 11 23:59
3	Antenna Rotation	rotated, stopped for macrocycle mode changes of Dec 8 and 9
4	Speckle Mode	True, Dec 7 - 11 False, Dec 12 - 20, Dec 8 18:19 - 18:40, and Dec 9 07:31 - 07:40
5	Temperatures and EDAC errors	The temperature profiles are nominal
6	Calibration 1	All the PTR calibration sequences are OK
7	Specific investigations	
8	Status	The SWIM altimeter performed well during this cycle



Color legend:


	OK
	Warning
	NOK

Part 4


Instrument mode and House Keeping

This part presents the instrument modes and the DPU cabin temperature for the current cycle (taken from the House Keeping telemetry data).





3




4

## Part 5

# CAL1 internal sequence


This part presents the major characteristics - total power, width, and position of the peak - of the main lobe of the Point Target Response (PTR), since cycle 22 (averaged within a 13-day sliding window).

The increase in the PTR total power on June 24 2020 is due to an update of the gain calibration table, made upon the change of AWWAIS version (4.3.2 to 5.0.1). Occasional PTR shifts are the cause of the troughs seen in the figure position of the maximum value. The origin of the shifts is still under investigation, though these do not affect the data.




5





6





7



## Part 6

# Antenna rotation speed

The following plots show the antenna rotation speed for the current cycle and since cycle 22 (averaged within a day). The antenna was stopped on October 24/25 2019 (cycle 28) during 24h for hardware behavior analysis, leading to the couple of points at low rotation speed seen in the bottom plot.



# Main Part III

## Coverage

## Part 7



# Coverage nadir 5Hz

Coverage is monitored by the presence flag, which gives the percentage of nadir points available in CFOSAT Level-2 products regardless of surface type. This information is obtained by comparing the 5Hz resolution time with the theoretical ground track.

**Missing data cycle 060** During a special program (antenna rotation stopped to target a reflector in the area of Toulouse) on December 8th, 2020 from 18:19 to 18:41, and on December 9th, 2020 from 07:24 to 07:46, SWIM was operated in a non-nominal mode ("0-8-8" mode). Missing data on December 9th, 2020 from 02:36 to 04:22, due to missing NADIR products.

Table 7.1: SWIM nadir 5Hz coverage

Percentage on current cycle	Cycle 60
Percentage of available measurements over ocean	99.86 %
Percentage of missing measurements over ocean	0.14 %



## Part 8



# Coverage off-nadir

Coverage is monitored by the presence flag, which gives the percentage of points available in CFOSAT Level-2 products regardless of surface type. This information is obtained by comparing the Box Left/Right time with the theoretical ground track.

**Missing data cycle 060** SWIM was operated in non-nominal modes (see page 8) from December 8th, 2020 at 00:00 to December 11th, 2020 at 23:59:59, resulting in missing data for the off-nadir beams. In addition, during a special program (antenna rotation stopped to target a reflector in the area of Toulouse) on December 8th, 2020 from 18:19 to 18:41, and on December 9th, 2020 from 07:24 to 07:46, SWIM was operated in a non-nominal mode ("0-8-8" mode).

Table 8.1: SWIM Box Left/Right coverage

Percentage on current cycle	Cycle 60
Percentage of available measurements over ocean	69.48 %
Percentage of missing measurements over ocean	30.52 %



# Main Part IV

## Editing

## Part 9

# Nadir 5Hz Nsec

The data are edited based on two types of criteria: quality (flag) and thresholds, both defined in the table below. The quality criterium is applied first. It is based on the SWH flag that is included in the Level-2 products and illustrated by the "Edited data by quality control" figure below. This flag takes into account surface (land) and sea-ice coverage at a threshold defined in the product attributes. As for the second criterium, thresholds on several variables are applied. Values outside minimal and maximal limits are rejected and are not taken into account in the statistical analyses.

Maps in this part represent data on land and ocean for the current cycle, whereas temporal monitorings are given on ocean only.

Table 9.1: Thresholds for data editing




Variables 5Hz	Min value	Max value
nadir_swh_native	0	20
nadir_swh_nsec_used	10	20
nadir_swh_nsec_std	0	$0.4 + \text{SWH.ALTI} * 0.028$
wind_speed	0	30
nadir_sigma0_nsec	5	25
nadir_sigma0_nsec_std	0	3.0
nadir_sigma0_nsec_used	10	20
flag_swh	0	0
ice_flag	0	0

Table 9.2: SWIM nadir 5Hz coverage


Percentage on current cycle	Cycle 60
Percentage of rejected points due to quality flag swh including product ice flag over ocean	18.76 %
Additionnal percentage of threshold rejection	1.74 %
Total percentage of rejected measurements over ocean	20.51 %

## Edited data by quality control

flag\_valid\_swh\_nsec != 0.00



The figure on the left represents rejected values based on the editing criteria listed in Table 9.1. The map shows the SWH values of rejected points in colour. When this representation is not possible (masked points, non-computed values) points are represented in black.



## Part 10

# Off-nadir

Editing is based on sea-ice and land coverage, as well as on thresholds on SWH, as described in the table below. It is applied to all Box Left/Right data. This editing will be improved over time.


Table 10.1: Thresholds for data editing

Variables Box LeftRight	Min value	Max value
swh masked per beam	non-default	non-default
sea-ice coverage per beam	0.0	0.0
land coverage per beam	0.0	0.0
swh per beam threshold	0.0	20.0

Table 10.2: Percentage of edited data



Variables	Beam 6	Beam 8	Beam 10	Combined
Total percentage of default value in the product over ocean	25.58 %	26.46 %	27.82 %	2.20 %
Additional ice rejection over all available measurements	0.00 %	0.00 %	0.00 %	12.67 %
Additional land rejection over all available measurements	0.54 %	0.69 %	0.77 %	11.56 %
Additional threshold rejection over ocean	0.00 %	0.00 %	0.00 %	0.00 %
Total percentage of rejected measurements over ocean	26.12 %	27.15 %	28.60 %	26.43 %

The following figures on the left show the percentage of rejected SWH points for beams 6°, 8° and 10° based on the editing criteria defined in Tables 10.1 and 10.2. The following maps on the right show, for beams 6°, 8° and 10°, the values of SWH (colors) that have been rejected. When this representation is not possible (masked points, non-computed values), the points are marked as black dots.







Total invalid data from beam 8 (not continental)



Total invalid data from beam 10 (not continental)



Main Part V


SWIM nadir monitoring

## Part 11


# Current cycle maps of valid SWH and wind speed

### 11.1 Current cycle map of valid SWH

Two types of nadir waves are monitored: native SWH and Nsec SWH. The native SWH is the output of the adaptive retracking at 5Hz resolution. The Nsec SWH is the native SWH compressed with a sliding window of N seconds; here Nsec has a 5Hz resolution. In this part, only valid data are assessed, i.e. all values rejected based on the editing described previously are not taken into account.



11.2 Current cycle map of wind speed




## Part 12

# SWIM nadir versus ECMWF model

The following figures compare SWH from SWIM nadir to that of the ECWMF model. The editing criteria applied to SWIM data are equally applied to ECMWF in order to perform a direct comparison.


### 12.1 Long term monitoring along track for SWH



### 12.2 Current cycle map of SWH difference with ECMWF model

This maps represent the difference SWIM nadir - ECMWF for the current cycle.

Significant wave height Nsec vs ECMWF differences




## Part 13

# Wind speed versus ECMWF model


The following figures compare the wind speed from SWIM nadir to that of the ECMWF model.

### 13.1 Long term monitoring along track for wind speed



### 13.2 Current cycle map of Wind speed difference with ECMWF model


This maps represent the difference Wind Nadir (Nsec) - ECMWF for the current cycle.



## Part 14

# CFOSAT/SWIM nadir versus AL and J3 at crossovers (3h)


Crossovers are computed between CFOSAT nadir/Altika and CFOSAT nadir/Jason-3, using a maximum time lag of 3 hours. The parameters SWH, sigma0, and wind are compared at the crossing points, and the corresponding differences are computed between two satellites (CFOSAT minus crossing satellite). The SWH validity flag is applied to Altika and Jason-3, and the editing described in Part 9 is applied to CFOSAT (cf. Table 9.1). The number of crossover points between Altika and CFOSAT is stable, whereas that between CFOSAT and Jason-3 varies due to Jason-3's orbit geometry, creating a subcycle of 120 days as seen in the figure below.



### 14.1 Long term monitoring along track SWH (CFO/AL/J3)

A change in Altika's mission ground segment, to standard-F, occurred during SWIM's cycle 38. This led to a variation in the SWH mean difference between the two satellites, from 4 to 10 cm, while the standard deviation remained stable. The change of Jason-3 to standard-F occurred during SWIM's cycle 57.






## 14.2 Long term monitoring along track sigma0 (CFO/AL/J3)


Since mid October 2019, SWIM has been affected by microcuts that occasionally and randomly lower the level of the radar echoes inside a macrocycle. This problem introduces a decrease in SWIM's sigma0, therefore an increase in the differences between satellites, seen in both the mean and standard deviation figures below (after the vertical line "Microcuts beginning"). Starting from cycle 47 (end of June 2020), a new variable that flags affected data is computed and included in the products.

Both CFOSAT and Jason-3 operate at Ku-band, whereas Altika operates at Ka-band, which explains the offset in the mean sigma0 differences between CFOSAT and Altika.



## 14.3 Long term monitoring along track wind (CFO/AL/J3)

Following SWIM's sigma0 variations due to the microcuts, the differences in wind between CFOSAT and Altika/Jason-3 also increased between cycles 27 and 45. These have nevertheless decreased since June 2020, when the change in SWIM's ground segment occurred (represented by the vertical line "AWWAIS 5.0.1" in the figures).



## Main Part VI


# SWIM off-nadir monitoring

## Part 15

# SWIM off-nadir current cycle maps per beam


## 15.1 SWH

SWH is retrieved from the spectra of beams 6°, 8° and 10°. This wave parameter is monitored in the following maps for the current cycle.




## 15.2 Wavelength

Peak wavelength is retrieved from the spectra of beams 6°, 8° and 10°. This wave parameter is monitored in the following maps for the current cycle.



### 15.3 Direction

Peak direction is retrieved from the spectra of beams 6°, 8° and 10°. This wave parameter is monitored in the following maps for the current cycle.



## Part 16

# SWIM off-nadir versus models

Two main events affect the time series shown below:


- at the beginning of the period concerned by the microcuts, the attenuation suffered by sigma0 affected the spectral distribution and thus the resulting estimated parameters;
- the introduction of the microcuts flagging and the evolution of the ground segment (e.g. MTF and speckle managing) upon the AWWAIS upgrade in June 2020.

The figures of difference represent Model values subtracked from SWIM.


### 16.1 SWIM SWH versus ECMWF SWH

SWIM's SWH from beams 6°, 8° and 10° are compared to those from the ECMWF model, at the colocated points given in the Level-2 products.

#### 16.1.1 Current cycle maps of differences with ECMWF model




## 16.1.2 Long term monitoring along track




## 16.2 SWIM wavelength versus MFWAM wavelength

SWIM's wavelengths from beams 6°, 8° and 10° are compared to those from the MFWAM model, at colocated points.

### 16.2.1 Current cycle maps of differences with MFWAM




### 16.2.2 Long term monitoring along track



## 16.3 SWIM direction versus MFWAM direction



SWIM's peak directions of partition 1 from beams 6°, 8° and 10° are compared to those from the MFWAM model, at colocated points. MFWAM's peak direction is calculated from the mean direction of swell 1. To be comparable, MFWAM's peak values have been transformed from direction (0 - 360) to orientation (0 - 180).

### 16.3.1 Current cycle maps of differences with MFWAM





## 16.3.2 Long term monitoring along track





## Part 17

# SWIM off-nadir versus Sentinel-1

Crossovers are computed between Sentinel-1 and CFOSAT SWIM off-nadir data. Crossover points are selected if:


- the distance between Sentinel-1 and CFOSAT spectra is less than 100 km;
- the time difference is less than 1 hour.

This leads to a specific pattern: Sentinel-1 and CFOSAT crossovers happen only in ascending CFOSAT passes.

The maps below show the along track differences between Sentinel-1 (most significant partition) and CFOSAT/SWIM per beam, for this cycle. The figures of difference represent Sentinel-1 values subtracked from SWIM.

### 17.1 SWH

The following figures show the SWH comparison between SWIM and Sentinel-1.



## 17.2 Wavelength

The following figures show the wavelength comparison between SWIM and Sentinel-1. Here, the largest differences are possibly due to intrinsic discrepancies in behaviour between the two instruments; this subject is under investigation.

